


PRODUCT FEATURES

- Ultrafast Reverse Recovery Time
- Soft Reverse Recovery Characteristics
- Low Reverse Recovery Loss
- Low Forward Voltage
- High Surge Current Capability
- Low Inductance Package



APPLICATIONS

- Inversion Welder
- Uninterruptible Power Supply (UPS)
- Plating Power Supply
- Ultrasonic Cleaner and Welder
- Converter & Chopper
- Power Factor Correction (PFC) Circuit



ABSOLUTE MAXIMUM RATINGS

$T_C=25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Values	Unit
V_R	Maximum D.C. Reverse Voltage		1200	V
V_{RRM}	Maximum Repetitive Reverse Voltage		1200	V
$I_{F(AV)}$	Average Forward Current	$T_C=110^\circ\text{C}$, Per Diode	200	A
		$T_C=120^\circ\text{C}$, 20KHz, Per Diode	150	A
$I_{F(RMS)}$	RMS Forward Current	$T_C=110^\circ\text{C}$, Per Diode	280	A
I_{FSM}	Non-Repetitive Surge Forward Current	$T_J=45^\circ\text{C}$, $t=10\text{ms}$, 50Hz, Sine	1800	A
		$T_J=45^\circ\text{C}$, $t=8.3\text{ms}$, 60Hz, Sine	1950	A
I^2t	I^2t (For Fusing)	$T_J=45^\circ\text{C}$, $t=10\text{ms}$, 50Hz, Sine	16200	A^2s
		$T_J=45^\circ\text{C}$, $t=8.3\text{ms}$, 60Hz, Sine	19012	A^2s
P_D	Power Dissipation		568	W
T_J	Junction Temperature		-40 to +150	$^\circ\text{C}$
T_{STG}	Storage Temperature Range		-40 to +125	$^\circ\text{C}$
V_{isol}	Insulation Test Voltage	AC, $t=1\text{min}$	3000	V
Torque	Module-to-Sink	Recommended (M6)	3~5	N·m
Torque	Module Electrodes	Recommended (M6)	3~5	N·m
$R_{\theta JC}$	Thermal Resistance	Junction-to-Case	0.22	$^\circ\text{C}/\text{W}$
Weight			160	g

ELECTRICAL CHARACTERISTICS

$T_C=25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
I_{RM}	Reverse Leakage Current	$V_R=1200V$	--	--	2	mA
		$V_R=1200V, T_J=125^\circ\text{C}$	--	--	10	mA
V_F	Forward Voltage	$I_F=200A$	--	2.3	--	V
		$I_F=200A, T_J=125^\circ\text{C}$	--	1.9	--	V
t_{rr}	Reverse Recovery Time	$I_F=1A, V_R=30V, di_F/dt=-200A/\mu s$	--	57	--	ns
t_{rr}	Reverse Recovery Time	$V_R=600V, I_F=200A$	--	110	--	ns
I_{RRM}	Max. Reverse Recovery Current		$di_F/dt=-200A/\mu s, T_J=25^\circ\text{C}$	--	9	--
t_{rr}	Reverse Recovery Time	$V_R=600V, I_F=200A$	--	500	--	ns
I_{RRM}	Max. Reverse Recovery Current		$di_F/dt=-200A/\mu s, T_J=125^\circ\text{C}$	--	21	--




Figure1. Forward Voltage Drop vs Forward Current




Figure2. Reverse Recovery Time vs di_F/dt




Figure3. Reverse Recovery Current vs di_F/dt




Figure4. Reverse Recovery Charge vs di_F/dt

**MMF200S120DK
MMF200S120DK2B**




Figure5. Dynamic Parameters vs Junction Temperature





Figure6. Transient Thermal Impedance



Dimensions (mm)
Figure7. Package Outline